

Prado

Garden

The Prado artificial grass, with a height of 50 mm, combines straight fibers with semi-texturized fibers, both featuring a triple-C cross-section and available in 5 shades of green. With Look&Feel technology, it achieves an impressively realistic appearance. The KDK technique used in its production ensures better resilience to foot traffic and shape memory with MaxRecover technology.

Its design promotes optimal drainage with MaxDrain technology, making it ideal for outdoor use, while its root-effect texturized fibers provide softness and comfort.

With an excellent quality/price ratio, it is child-safe, non-flammable, and bacteria-resistant, making it the perfect choice for residential gardens. Furthermore, it is easy to maintain, durable, and resistant.



- ▲ Triple C Monofilament
- ▲ Look&Feel fibers
- ▲ Green and beige curl
- ▲ Height: 50 mm



Specifications



General Data

Colour	5 tones green with beige and green curl
Roll size	2x20 m 4x20 m

Specifications

Composition	Polyethylene and Polypropylene in curl
Type	Triple C-shaped Monofil.
Dtex	18,000
Pile Height	50 mm
Gauge	5/8"
Stitches/m ²	8,505
Fiber Weight	1,692 g/m ²
Total Weight	2,992 g/m ²
Primary Backing	Polypropylene
Secondary Backing	Latex

Test and certificates

DURABILITY

UV Stability Scale >3 (UNE-EN 20105-A02)
Permeability up to 65 l/min/m² (UNE-EN 12616:2014)
Chlorinated water stability (ISO 105-E 03:2010)

SECURITY 100%

Bacteria free (ASTM G 21:2013)
Non toxic (EN 71-3)
Non flammable (EN 13501 Cfl-s1)

ECO

Zero Waste
ISO 14.001
100% Recyclable (CSIC)

Infill

Recommended infill from 10 to 15mm Stabilization.

realturf



Av. Antigua Peseta, 131
Polígono Industrial las Atalayas
03114 Alicante
+34 965 685 640 / +34 900 908 150
realturf@realturf.com

Review: 2
Data of approval: 19/02/2025

Realturf Systems, S.L. reserves the right to modify the technical characteristics of the product described. The declared values will admit the tolerances established by the ISO regulation that it should apply in every case. Realturf Systems, S.L. guarantees the technical quality of the product.

