

Golf Putt

Golf

Golf Putt is a 12 mm high artificial grass with texturized threads, perfect to use in both professional and residential putting greens, because of its performance both at the reception and the rolling of the ball.

The product is manufactured with the in-line tufting system with a 3/16 inches gauge between stitches, 48,500 per square meter, and a total weight of 2,650 g/m². Its fibers have an anti-UV treatment which gives an excellent and resistant finishing for the most demanding weather conditions.

A silica sand filling (round, washed and dried 0.2 - 1.0 mm) with about 8 - 10 kg/m² is recommended.

Available colours:

▲ Green ▲ Blue ▲ Red ▲ Black ▲ Rust ▲ White



Specifications

General Data

Colour	Green, blue, red, black, rust, white
Roll size	2,02 x20,50 m

Specifications

Composition	Polyethylene
Type	Textured monofilament
Dtex	8,800 (±10%)
Pile Height	12 mm (±5%)
Gauge	3/16"
Stitches/m ²	48,500 (±10%)
Fiber Weight	1,300 g/m ² (±10%)
Total Weight	2,650 g/m ² (±10%)
Primary Backing	Polypropylene
Secondary Backing	Latex

Test and certificates

DURABILITY

UV Stability Scale >3 (UNE-EN 20105-A02)
Permeability 32.5 l/min/m² (UNE-EN 12616:2014)
Chlorinated water stability (ISO 105-E 03:2010)

SECURITY 100%

Bacteria free (ASTM G 21:2013)
Non toxic (EN 71-3)
Non flammable (EN 13501 Cfl-s1)

ECO

Zero Waste
ISO 14.001
100% Recyclable (CSIC)

Infill

Material	Round Silica sand
Granulometry	0.20 - 1.00 mm
Application dose	8 -10 kg/m ²

realturf



Av. Antigua Peseta, 131
Polígono Industrial las Atalayas
03114 Alicante
Tel. 965 685 640 / 900 908 150
realturf@realturf.com

Review: 1
Date of approval: 11/02/2025

Realturf Systems, S.L. reserves the right to modify the technical characteristics of the product described.
The declared values will admit the tolerances established by the ISO regulation that it should apply in every case.
Realturf Systems, S.L. guarantees the technical quality of the product.

